

Standard Features

- 1 3/4" thick
- Any manufacturer's hinge locations
- 16-gauge A40 galvanized steel standard
- ANSI A250.8 Model 2, continuously welded vertical edges (seamless) standard
- Rust inhibitive prime coat meets ANSI/SDI A250.10
- Tested in accordance with UL 752, Level 1 through 8 for ballistic products
- Bullet resistant frames available

Material Options

- 14-gauge
- A60, G90, CRS

Feature Options

- Channeled lite cutout only*
- Flush top cap
- Any manufacturer's deadlock prep, panic prep, and mortise sectional trim










Hardware Reinforcements

- 3/16" for hinges
- 12-gauge for locks standard
- 14-gauge for closers standard
- Heavier gauge reinforcements available

**To be used with third-party aftermarket bullet resistant lite kit.*



THREAT LEVELS

LEVEL	BULLET	CALIBER	SHOTS
1		9mm (124g) FMJ	3
2		.357 Magnum (158g) SP	3
3		.44 Magnum (244g) SP	3
4		.30 Caliber Rifle (180g) SP	1
5		7.62mm Rifle (150g) FMJ	1
6		9mm Multi (124g) FMJ	5
7		5.56mm Rifle (55g)	5
8		7.62mm Multi Rifle (150g) FMJ	5
8 (AP)		30-06 Rifle (166g)	5