

3-Sided Frame w/Sidelite & Transom

Material *

Construction *

Gauge *

All fields marked with an asterisk are prepopulated to DCI standards.

Panels

Door Side
Oppo. Door Side

Glass Stop

Door Side
Oppo. Door Side

TO TOP OF HINGE

OPTIONAL 4TH HINGE

OPENING WIDTH

Jamb Depth

Throat Size

Door Side Flange
(optional)

STUD SIZE:

HINGE LOCATIONS

HINGE
TYPE

HINGE
DETAILS:

STRIKE
TYPE:

STRIKE
DETAILS:

NOTE: All frames include door closer reinforcement.
All welded frames include A4 standard base anchors.

OTHER DETAILS:

* BACKSET *

*
STD WEIGHT
HEAVY WEIGHT

SILENCERS:

Any non-standard transom profile, supply additional detail

ANCHOR TYPE:

For a full description of all DCI anchor types,
please refer to our [Technical Data Manual](#).

All stud anchors will be spaced for 5/8" wall board
penetration unless otherwise noted



www.dcihollowmetal.com

COMPANY NAME :

PO NUMBER :

JOB NAME :

PAGE

OF

3-Sided Frame w/Sidelite & Transom

Material *

Construction *

Gauge *

All fields marked with an asterisk are prepopulated to DCI standards.

Panels

Door Side
Oppo. Door Side

Glass Stop

Door Side
Oppo. Door Side

TO TOP OF HINGE

OPTIONAL 4TH HINGE

OPENING WIDTH

Jamb Depth

Throat Size

Door Side Flange
(optional)

STUD SIZE:

HINGE LOCATIONS

HINGE
TYPE

HINGE
DETAILS:

STRIKE
TYPE:

STRIKE
DETAILS:

NOTE: All frames include door closer reinforcement.
All welded frames include A4 standard base anchors.

OTHER DETAILS:

* BACKSET *

*
STD WEIGHT
HEAVY WEIGHT

SILENCERS:

Any non-standard transom profile, supply additional detail

ANCHOR TYPE:

For a full description of all DCI anchor types,
please refer to our [Technical Data Manual](#).

All stud anchors will be spaced for 5/8" wall board
penetration unless otherwise noted



www.dcihollowmetal.com

COMPANY NAME :

PO NUMBER :

JOB NAME :

PAGE

OF

3-Sided Frame w/Sidelite & Transom

Material *

Construction *

Gauge *

All fields marked with an asterisk are prepopulated to DCI standards.

Panels

Door Side
Oppo. Door Side

Glass Stop

Door Side
Oppo. Door Side

TO TOP OF HINGE

OPTIONAL 4TH HINGE

OPENING WIDTH

Jamb Depth

Throat Size

Door Side Flange
(optional)

STUD SIZE:

HINGE LOCATIONS

HINGE
TYPE

HINGE
DETAILS:

STRIKE
TYPE:

STRIKE
DETAILS:

NOTE: All frames include door closer reinforcement.
All welded frames include A4 standard base anchors.

OTHER DETAILS:

* BACKSET *

*
STD WEIGHT
HEAVY WEIGHT

SILENCERS:

Any non-standard transom profile, supply additional detail

ANCHOR TYPE:

For a full description of all DCI anchor types,
please refer to our [Technical Data Manual](#).

All stud anchors will be spaced for 5/8" wall board
penetration unless otherwise noted



www.dcihollowmetal.com

COMPANY NAME :

PO NUMBER :

JOB NAME :

PAGE

OF